

QMTS2.E123995 - Polymeric Materials - Filament-wound Tubing, Industrial Laminates, Vulcanized Fiber, and Materials for Use in Fabricating Recognized Printed Wiring Boards - Component

Polymeric Materials - Filament-wound Tubing, Industrial Laminates, Vulcanized Fiber, and Materials for Use in Fabricating Recognized Printed Wiring Boards - Component

See General Information for Polymeric Materials - Filament-wound Tubing, Industrial Laminates, Vulcanized Fiber, and Materials for Use in Fabricating Recognized Printed Wiring Boards - Component

KINGBOARD LAMINATES HOLDINGS LTD

E123995

23/F., DELTA HOUSE
NO. 3 ON YIU STREET
SHATIN, N T HONG KONG

Industrial laminates:

Mtl Dsg	ANSI Type	Color	Build up	Flame Class	R.T.I.		H				Meets 746E Non-HAL	Meets 746E DSR
			Min Thk (mm)		Elec (°C)	Mech (°C)	H W I	H A I	V T R	C T I		
Industrial laminates, furnished as sheets.												
KB-150	XPC	NC, BK	0.71	HB	130	130	2	0	0	-	-	Yes
			1.57	HB	130	130	1	0	1	4	-	Yes
KB-2150	FR-2	NC	1.45	V-0	105	105	4	3	1	4	-	Yes
KB-2150G	FR-2	TN	0.71	V-0	75	75	0	3	6	-	-	Yes
			1.45	V-0	105	105	0	3	6	3	-	Yes
KB-2150GC	FR-2	TN	0.71	V-0	75	75	0	4	6	-	-	-

			1.45	V-0	105	105	0	3	6	0	-	Yes
KB-3151S (with Adhesive)												
	FR-1	NC	1.45	V-0	130	130	0	0	-	0	-	Yes
			0.71	V-0	130	130	0	0	-	-	-	Yes
KB-3151S (without Adhesive)												
	FR-1	NC	1.45	V-0	130	130	3	3	4	4	-	Yes
			0.71	V-0	130	130	3	3	4	-	-	Yes
KB-3152	FR-1	NC	0.71	V-0	130	130	0	0	-	-	-	Yes
			1.45	V-0	130	130	0	0	-	0	-	Yes
KB-5150	CEM-1	NC	0.63	V-0	130	140	3	2	4	-	-	Yes
			1.40	V-0	130	140	1	2	4	3	-	Yes
KB-5150&												
	CEM-1	NC	0.63	V-0	130	140	1	3	4	-	-	Yes
			1.40	V-0	130	140	1	3	4	0	-	Yes
KB-5252	CEM-1	NC	0.63	V-0	130	140	3	2	-	-	-	Yes
			1.40	V-0	130	140	1	2	-	3	-	Yes
KB-6150C	FR-4.0	NC	0.63	V-0	130	140	0	3	4	-	-	Yes
			1.40	V-0	130	140	0	2	4	0	-	Yes
KB-6160A	FR-4.0	YL	0.38	V-0	130	130	0	0	-	-	-	Yes
			0.63	V-0	130	140	0	3	4	-	-	Yes
			1.40	V-0	130	140	0	2	4	3	-	Yes
KB-6160C	FR-4.0	NC	0.38	V-0	130	130	0	0	-	-	-	Yes
			0.63	V-0	130	140	0	3	4	-	-	Yes

			1.40	V-0	130	140	0	2	4	0	-	Yes
KB-6160F	FR-4.0	NC	0.38	V-0	130	130	0	1	-	-	-	Yes
			0.63	V-0	130	140	0	1	-	-	-	Yes
			1.40	V-0	130	140	0	1	-	3	-	Yes
KB-6165	FR-4.0	YL	0.38	V-0	130	130	2	0	-	-	-	Yes
			0.63	V-0	130	140	0	3	4	-	-	Yes
			1.40	V-0	130	140	0	2	4	3	-	Yes
KB-6165G	FR-4.1	NC	0.05	V-0	120	100	0	3	-	-	Yes	Yes
			0.38	V-0	130	130	0	1	-	-	-	Yes
			0.63	V-0	130	140	0	1	-	-	-	Yes
			1.40	V-0	130	140	0	1	-	3	-	Yes
KB-6165GC	FR-4.1	NC	0.05	V-0	120	100	0	3	-	-	Yes	Yes
			0.38	V-0	130	130	0	1	-	-	-	Yes
			0.63	V-0	130	140	0	1	-	-	-	Yes
			1.40	V-0	130	140	0	1	-	0	-	Yes
KB-6165GT	FR-15.1	NC	0.38	V-0	140	140	0	1	-	-	Yes	Yes
			0.63	V-0	150	150	0	1	-	-	-	Yes
			1.40	V-0	150	150	0	1	-	0	-	Yes
KB-6168	FR-4.0	NC	0.38	V-0	130	130	0	3	-	-	-	Yes
			0.63	V-0	130	140	0	3	4	-	-	Yes
			1.40	V-0	130	140	0	2	4	3	-	Yes
KB-7150	CEM-3.0	NC	0.63	V-0	130	140	0	2	4	-	-	Yes
			1.40	V-0	130	140	0	2	4	3	-	Yes

KB-7150C	CEM-3.0	NC	0.63	V-0	130	140	0	2	4	-	-	Yes
			1.40	V-0	130	140	0	2	4	0	-	Yes
Industrial laminates, furnished as sheets or rolls.												
KB-5150A	CEM-1	NC	0.63	V-0	130	140	3	2	4	-	-	Yes
			1.40	V-0	130	140	1	2	4	2	-	Yes
KB-5150G	CEM-1	NC	0.63	V-0	130	140	3	2	4	-	-	Yes
			1.40	V-0	130	140	1	2	4	0	-	Yes
KB-5150H	CEM-1	NC	0.63	V-0	130	140	3	2	4	-	-	Yes
			1.40	V-0	130	140	1	2	4	2	-	Yes
KB-5150L	CEM-1	NC	0.63	V-0	130	140	3	2	4	-	-	Yes
			1.40	V-0	130	140	1	2	4	3	-	Yes
KB-616(X)	FR-4.0	YL	0.38	V-0	130	130	3	3	-	-	-	Yes
			0.63	V-0	130	140	0	3	4	-	-	Yes
			1.40	V-0	130	140	0	2	4	3	-	Yes
KB-6163F	FR-4.0	NC	0.38	V-0	130	130	1	1	-	-	-	Yes
			0.63	V-0	130	140	0	1	-	-	-	Yes
			1.40	V-0	130	140	0	1	-	3	-	Yes
KB-6164F	FR-4.0	NC	0.38	V-0	130	130	0	4	-	-	-	-
			0.63	V-0	130	140	0	2	-	-	-	Yes
			1.40	V-0	130	140	0	1	-	3	-	Yes
KB-6165F	FR-4.0	NC(YL)	0.38	V-0	130	130	3	3	-	-	-	Yes
			0.63	V-0	130	140	0	3	4	-	-	Yes

			1.40	V-0	130	140	0	2	4	3	-	Yes
KB-6167A	FR-4.0	NC	0.38	V-0	130	130	0	2	-	-	-	Yes
			0.63	V-0	130	140	0	2	4	-	-	Yes
			1.40	V-0	130	140	0	1	4	4	-	Yes
KB-6167F	FR-4.0	NC	0.38	V-0	130	130	0	3	-	-	-	Yes
			0.63	V-0	130	140	0	3	4	-	-	Yes
			1.40	V-0	130	140	0	2	4	3	-	Yes
KB-6167G	FR-4.1	NC	0.05	V-0	120	100	0	3	-	-	Yes	Yes
			0.38	V-0	130	130	0	1	-	-	-	Yes
			0.63	V-0	130	140	0	1	-	-	-	Yes
			1.40	V-0	130	140	0	1	-	0	-	Yes
KB-6167GMD												
	FR-4.1	NC	0.38	V-0	130	130	0	1	-	-	Yes	Yes
			0.63	V-0	130	140	0	1	-	-	-	Yes
			1.40	V-0	130	140	0	0	-	0	-	Yes
KB-7150T	CEM-3.0	NC	0.63	V-0	130	140	0	2	4	-	-	Yes
			1.40	V-0	130	140	0	2	4	0	-	Yes
Industrial laminates, furnished as sheets, rods or tubes.												
HF-140	FR-4.1	NC	0.38	V-0	130	130	0	2	-	-	Yes	Yes
			0.63	V-0	130	140	0	2	-	-	-	Yes
			1.40	V-0	130	140	0	2	-	3	-	Yes
KB-3150N	FR-1	NC	0.71	V-0	130	130	0	0	-	-	-	Yes

			1.45	V-0	130	130	-	-	-	3	-	Yes
KB-3150NU %												
	FR-1	NC	0.71	V-0	130	130	3	3	4	-	-	Yes
			1.45	V-0	130	130	3	3	4	4	-	Yes
KB-3151HS	FR-1	NC	0.71	V-0	130	130	0	0	4	-	-	Yes
			1.45	V-0	130	130	0	0	4	0	-	Yes
KB-3152C	FR-1	NC	0.71	V-0	130	130	0	0	4	-	-	Yes
			1.45	V-0	130	130	0	0	4	0	-	Yes
KB-3152S	FR-1	NC	0.71	V-0	130	130	0	0	4	-	-	Yes
			1.45	V-0	130	130	0	0	4	0	-	Yes
KB-3153*	FR-1	NC	0.71	V-0	130	130	0	0	4	-	-	Yes
			1.45	V-0	130	130	0	0	4	0	-	Yes
KB-5152	No ANSI	NC	0.60	V-0	-	-	-	-	-	-	-	-
			1.40	V-0	-	-	-	-	-	-	-	-
KB-6150	FR-4.0	NC	0.10	V-0	120	125	0	3	-	-	-	Yes
			0.63	V-0	130	140	0	3	4	-	-	Yes
			1.40	V-0	130	140	0	2	4	4	-	Yes
			0.38	V-0	130	130	0	3	-	-	-	Yes
KB-6162	No ANSI	NC	0.63	V-0	-	-	-	-	-	-	-	-
			1.40	V-0	-	-	-	-	-	-	-	-
KB-6167GLD												
	FR-4.1	NC	0.38	V-0	130	130	0	3	-	-	Yes	Yes
			0.63	V-0	130	140	0	3	-	-	-	Yes

			1.40	V-0	130	140	0	2	-	3	-	Yes
Industrial laminates.												
EEL-128	FR-4.0	NC	0.38	V-0	130	130	3	0	-	-	-	-
			0.63	V-0	130	140	0	3	-	-	-	Yes
			1.40	V-0	130	140	0	2	-	3	-	Yes
EEL-145	FR-4.0	NC	0.38	V-0	130	130	3	0	-	-	-	-
			0.63	V-0	130	140	0	3	-	-	-	Yes
			1.40	V-0	130	140	0	2	-	3	-	Yes
KB-3151C (with Adhesive)												
	FR-1	NC	0.71	V-0	130	130	0	0	-	-	-	Yes
			1.45	V-0	130	130	-	-	-	0	-	Yes
KB-3151C (without Adhesive)												
	FR-1	NC	0.71	V-0	130	130	3	3	4	-	-	Yes
			1.45	V-0	130	130	3	3	4	4	-	Yes
KB-3151C175 (with Adhesive)												
	FR-1	NC	0.71	V-0	130	130	0	0	-	-	-	Yes
			1.45	V-0	130	130	-	-	-	3	-	Yes
KB-6155	FR-4.0	NC	0.38	V-0	130	130	0	3	-	-	-	Yes
			0.63	V-0	130	140	0	3	4	-	-	Yes
			1.40	V-0	130	140	0	2	4	4	-	Yes
KB-6165GLD												
	FR-4.1	NC	0.38	V-0	130	130	0	0	-	-	Yes	Yes

			0.63	V-0	130	140	0	0	-	-	-	Yes
			1.40	V-0	130	140	0	1	-	3	-	Yes
KB-6165GMD												
	FR-4.1	NC	0.38	V-0	130	130	0	0	-	-	Yes	Yes
			0.63	V-0	130	140	0	1	-	-	-	Yes
			1.40	V-0	130	140	0	1	-	2	-	Yes
KB-7152	CEM-3.0	NC	0.63	V-0	130	140	0	2	4	-	-	Yes
			1.40	V-0	130	140	0	2	4	3	-	Yes

Ultrathin build ups:

	Build Up				Laminate				Prepreg		
	Mtl Dsg	ANSI Type	Min Thk (mm)	TI Elec	TI Mech	Mtl Dsg	Thk (mic)	TI Elec	Mtl Dsg	Thk (mic)	TI Elec
Ultrathin industrial laminates and bonding layers, furnished in sheet form, for use in multilayer printed wiring boards where the thickness is built up to the minimum specified.											
EEL-128	FR-4.0	0.38	130	130	EEL-128	50	90	EP		50	90
EEL-145	FR-4.0	0.38	130	130	EEL-145	50	90	ETP		50	90
HF-140	FR-4.1	0.38	130	130	HF-140	50	90	PP-HF140		50	90
KB-6155	FR-4.0	0.38	130	130	KB-6155	50	90	KB-6055		50	90
KB-616(X)	FR-4.0	0.38	130	130	KB-6160, KB-6164	100	120	KB-6060, KB-6064		50	90
KB-6160A	FR-4.0	0.38	130	130	KB-6160A	50	90	KB-6060A		50	90
KB-6160C	FR-4.0	0.38	130	130	KB-6160C	50	90	KB-6060C		50	90
KB-6160F	FR-4.0	0.38	130	130	KB-6160F	50	90	KB-6060F		50	90
		0.45	130	130	KB-6160F	50	90	KB-6060F		50	90

		0.63	130	140	KB-6160F	50	90	KB-6060F	50	90
		1.40	130	140	KB-6160F	50	90	KB-6060F	50	90
KB-6163F	FR-4.0	0.38	130	130	KB-6163F	50	90	KB-6063F	50	90
		0.45	130	130	KB-6163F	50	90	KB-6063F	50	90
		0.63	130	140	KB-6163F	50	90	KB-6063F	50	90
		1.40	130	140	KB-6163F	50	90	KB-6063F	50	90
KB-6164F	FR-4.0	0.38	130	130	KB-6164F	50	90	KB-6064F	50	90
KB-6165	FR-4.0	0.38	130	130	KB-6165	50	90	KB-6065	50	90
KB-6165F	FR-4.0	0.38	130	130	KB-6165F	50	90	KB-6065F	50	90
KB-6165G	FR-4.1	0.38	130	130	KB-6165G	50	90	KB-6065G	50	90
		0.63	130	140	KB-6165G	50	90	KB-6065G	50	90
KB-6165GC	FR-4.1	0.38	130	130	KB-6165GC	50	90	KB-6065GC	50	90
		0.63	130	140	KB-6165GC	50	90	KB-6065GC	50	90
KB-6165GLD	FR-4.1	0.38	130	130	KB-6165GLD	65	90	KB-6065GLD	50	90
KB-6165GMD	FR-4.1	0.38	130	130	KB-6165GMD	65	90	KB-6065GMD	50	90
KB-6165GT	FR-15.1	0.38	140	140	KB-6165GT	50	90	KB-6065GT	50	90
		0.63	150	150	KB-6165GT	50	90	KB-6065GT	50	90
KB-6167A	FR-4.0	0.38	130	130	KB-6167A	100	120	KB-6067A	50	90
KB-6167F	FR-4.0	0.38	130	130	KB-6167F	100	90	KB-6067F	50	90
KB-6167G	FR-4.1	0.38	130	130	KB-6167G	50	90	KB-6067G	50	90
KB-6167GLD	FR-4.1	0.38	130	130	KB-6167GLD	65	90	KB-6067GLD	50	90
KB-6167GMD	FR-4.1	0.38	130	130	KB-6167GMD	65	90	KB-6067GMD	50	90
KB-6168	FR-4.0	0.38	130	130	KB-6168	50	90	KB-6068	50	90

Metal clad industrial laminates:

Metal Clad Dsg	Lam- inate Dsg	Pre- preg Dsg	ANSI Type	Bld	Clad Cond Thk			Max	Area Dia	Flame Class	Max Oper Temp (°C)	Max Solder Temp (°C)	Solder Lts Time (sec)
				up	Min Thk (mm)	Min Ext (mic)	Max Ext (mic)	Max Int (mic)					
Metal clad industrial laminates for use in multilayer printed wiring boards with copper on one or both sides, furnished as sheets.													
KB-6160A													
	KB-6160A	KB-6060A	FR-4.0	0.38	12	102	70	50.8	V-0	130	288	20	
KB-6160C													
	KB-6160C	KB-6060C	FR-4.0	0.38	12	102	60	50.8	V-0	130	288	20	
KB-6160F													
	KB-6160F	KB-6060F	FR-4.0	0.38	9	102	68	50.8	V-0	130	288	30	
				0.45	12	102	102	50.8	V-0	130	288	30	
KB-6163F													
	KB-6163F	KB-6063F	FR-4.0	0.38	9	102	68	50.8	V-0	130	288	30	
				0.45	9	102	102	50.8	V-0	130	288	30	
KB-6164F													
	KB-6164F	KB-6064F	FR-4.0	0.38	12	102	102	50.8	V-0	130	288	60	
KB-6165													
	KB-6165	KB-6065	FR-4.0	0.38	12	102	54	50.8	V-0	130	288	60	
KB-6165F													
	KB-6165F	KB-6065F	FR-4.0	0.38	12	102	102	50.8	V-0	130	288	60	
				0.63	12	102	204	50.8	V-0	130	288	60	

KB-6165G													
	KB-6165G	KB-6065G	FR-4.1	0.38	12	102	102	50.8	V-0	130	288	20	
KB-6165GC													
	KB-6165GC	KB-6065GC	FR-4.1	0.38	12	102	102	50.8	V-0	130	288	20	
KB-6165GT													
	KB-6165GT	KB-6065GT	FR-15.1	0.38	12	102	102	50.8	V-0	130	288	20	
KB-6167F													
	KB-6167F	KB-6067F	FR-4.0	0.38	12	102	102	50.8	V-0	130	288	60	
KB-6167G/KB-6067G													
	KB-6167G	KB-6067G	FR-4.1	0.38	12	102	102	50.8	V-0	130	288	20	
KB-6168													
	KB-6168	KB-6068	FR-4.0	0.38	12	102	70	50.8	V-0	130	288	60	
Metal clad industrial laminates for use in multilayer printed wiring boards with copper on one or both sides, furnished as sheets or rolls.													
KB-616(X)													
	KB-6160, KB-6164	KB-6060, KB-6064	FR-4.0	0.38	17	102	35	50.8	V-0	130	288	30	
KB-6167A													
	KB-6167A	KB-6067A	FR-4.0	0.38	17	102	35	50.8	V-0	130	288	30	
Metal clad industrial laminates for use in multilayer printed wiring boards with copper on one or both sides, furnished as sheets, rods or tubes.													
HF-140													
	HF-140	PP-HF140	FR-4.1	0.38	12	102	102	50.8	V-0	130	288	30	
KB-6167GLD/KB-6067GLD, KB-6165GMD/KB-6065GMD, KB-6165GLD/KB-6065GLD and KB-6167GMD/KB-6067GMD													

	KB-6167GLD, KB-6165GMD, KB-6165GLD, KB-6167GMD	KB-6067GLD, KB-6065GMD, KB-6065GLD, KB-6067GMD	FR-4.1	0.38	12	102	102	50.8	V-0	130	288	30
Metal clad industrial laminates for use in multilayer printed wiring boards with copper on one or both sides.												
EEL-128												
	EEL-128	EP	FR-4.0	0.38	17	102	68	38.1	V-0	130	288	30
				0.63	17	102	68	50.8	V-0	130	288	30
EEL-145												
	EEL-145	ETP	FR-4.0	0.38	17	102	170	50.8	V-0	130	288	30
Metal clad industrial laminates for use in single layer printed wiring boards with copper on one or both sides, furnished as sheets.												
KB-2150G												
	KB-2150G	-	FR-2	0.71	35	102	-	50.8	V-0	75	265	15
				1.45	35	102	-	38.1	V-0	105	265	15
KB-2150GC												
	KB-2150GC	-	FR-2	0.71	35	102	-	50.8	V-0	75	265	15
				1.45	35	102	-	50.8	V-0	105	265	15
KB-3152												
	KB-3152	-	FR-1	0.71	35	102	-	50.8	V-0	130	288	10
KB-5150												
	KB-5150	-	CEM-1	0.63	17	102	-	38.1	V-0	130	288	20
KB-5252												
	KB-5252	-	CEM-1	0.63	17	102	-	13	V-0	130	260	10

KB-6150													
	KB-6150	-	FR-4.0	0.63	17	102	-	50.8	V-0	130	288	20	
KB-6150C													
	KB-6150C	-	FR-4.0	0.63	17	102	-	50.8	V-0	130	288	20	
KB-616(X)													
	KB-6160, KB-6164	-	FR-4.0	0.38	17	102	-	50.8	V-0	130	288	30	
KB-6160A													
	KB-6160A	-	FR-4.0	0.38	12	140	-	50.8	V-0	130	288	20	
KB-6160C													
	KB-6160C	-	FR-4.0	0.38	12	102	-	50.8	V-0	130	288	20	
KB-6160F													
	KB-6160F	-	FR-4.0	0.38	9	102	-	50.8	V-0	130	288	30	
KB-6163F													
	KB-6163F	-	FR-4.0	0.38	9	102	-	50.8	V-0	130	288	30	
KB-6164F													
	KB-6164F	-	FR-4.0	0.38	12	102	-	50.8	V-0	130	288	60	
KB-6165													
	KB-6165	-	FR-4.0	0.38	12	102	-	50.8	V-0	130	288	60	
KB-6165F													
	KB-6165F	-	FR-4.0	0.38	12	102	-	50.8	V-0	130	288	60	
KB-6165G													
	KB-6165G	-	FR-4.1	0.05	17	102	-	50.8	V-0	100	288	20	
				0.38	17	102	-	50.8	V-0	130	288	20	

KB-6165GC													
	KB-6165GC	-	FR-4.1	0.05	17	102	-	50.8	V-0	100	288	20	
				0.38	17	102	-	50.8	V-0	130	288	20	
KB-6165GT													
	KB-6165GT	-	FR-15.1	0.38	17	102	-	50.8	V-0	130	288	20	
KB-6167A													
	KB-6167A	-	FR-4.0	0.38	17	102	-	50.8	V-0	130	288	30	
KB-6167F													
	KB-6167F	-	FR-4.0	0.38	12	102	-	50.8	V-0	130	288	60	
KB-6167G													
	KB-6167G	-	FR-4.1	0.05	17	102	-	50.8	V-0	100	288	20	
				0.38	17	102	-	50.8	V-0	130	288	20	
KB-6168													
	KB-6168	-	FR-4.0	0.38	12	102	-	50.8	V-0	130	288	60	
KB-7150													
	KB-7150	-	CEM-3.0	0.63	17	102	-	50.8	V-0	130	290	20	
KB-7150C													
	KB-7150C	-	CEM-3.0	0.63	17	102	-	50.8	V-0	130	288	20	
KB-7150T													
	KB-7150T	-	CEM-3.0	0.63	17	102	-	50.8	V-0	130	288	20	

Metal clad industrial laminates for use in single layer printed wiring boards with copper on one or both sides, furnished as sheets, rods or tubes.													
HF-140													
	HF-140	-	FR-4.1	0.38	12	102	-	50.8	V-0	130	288	30	
KB-3152C													
	KB-3152C	-	FR-1	0.71	34	102	-	50.8	V-0	130	260	10	
KB-3152S													
	KB-3152S	-	FR-1	0.71	34	102	-	50.8	V-0	130	260	10	
KB-3153*													
	KB-3153	-	FR-1	0.71	34	102	-	50.8	V-0	130	260	10	
KB-6167GLD,KB-6165GMD,KB-6165GLD,KB-6167GMD													
	KB-6167GLD, KB-6165GMD, KB-6165GLD, KB-6167GMD	-	FR-4.1	0.38	12	102	-	50.8	V-0	130	288	30	
Metal clad industrial laminates for use in single layer printed wiring boards with copper on one or both sides.													
EEL-128													
	EEL-128	-	FR-4.0	0.38	17	102	-	38.1	V-0	130	288	30	
				0.63	17	102	-	50.8	V-0	130	288	30	
EEL-145													
	EEL-145	-	FR-4.0	0.38	17	102	-	50.8	V-0	130	288	30	
KB-3151C*													
	KB-3151C	-	FR-1	0.71	17	102	-	50.8	V-0	130	260	10	
KB-3151S													
	KB-3151S	-	FR-1	0.71	17	102	-	38.1	V-0	130	260	10	

KB-5150A												
	KB-5150A	-	CEM-1	0.63	17	102	-	50.8	V-0	130	288	20
KB-5150H												
	KB-5150H	-	CEM-1	0.63	17	102	-	50.8	V-0	130	288	20
KB-5150L												
	KB-5150L	-	CEM-1	0.63	17	102	-	50.8	V-0	130	260	10
KB-6155												
	KB-6155	-	FR-4.0	0.38	12	102	-	50.8	V-0	130	288	60
KB-7152												
	KB-7152	-	CEM-3.0	0.63	17	102	-	50.8	V-0	130	288	20
Metal clad industrial laminates for use in single layer printed wiring boards with copper on one side only, furnished as sheets.												
KB-1150												
	KB-150	-	XPC	0.71	35	117	-	25.4	HB	130	260	10
KB-5150												
	KB-5150	-	CEM-1	0.63	35	102	-	50.8	V-0	130	260	10
KB-5150G												
	KB-5150G	-	CEM-1	0.63	17	102	-	50.8	V-0	130	288	10
KB-5252												

	KB-5252	-	CEM-1	0.63	17	102	-	50.8	V-0	130	288	10
Metal clad industrial laminates for use in single layer printed wiring boards with copper on one side only, furnished as sheets, rods or tubes.												
KB-3150N												
	KB-3150NU %	-	FR-1	0.71	17	102	-	50.8	V-0	130	260	10
KB-3151HS												
	KB-3151HS	-	FR-1	0.71	34	102	-	50.8	V-0	130	260	10
Metal clad industrial laminates for use in multilayer printed wiring boards with copper on one or both sides.												
KB-6155												
	KB-6155	KB-6055	FR-4.0	0.38	12	102	70	50.8	V-0	130	288	60

Metal clad industrial laminates (Flammability Only Recognition):

Metal Clad Dsg	Lam-inate Dsg	Pre-preg Dsg	ANSI Type	Bld up	Clad Cond Thk			Max	Flame Class	Max	Solder Lts	
				Min Thk (mm)	Min Ext (mic)	Max Ext (mic)	Max Int (mic)	Area Dia (mm)		Oper Temp (°C)	Temp (°C)	Time (sec)
Metal clad industrial laminates for use in single layer printed wiring boards with copper on one or both sides, furnished as sheets (Flammability Only Recognition).												
KB-5152												
	KB-5152	-	No ANSI	0.60	-	-	-	-	V-0	-	260	10
KB-6162												
	KB-6162	-	No ANSI	0.63	-	-	-	-	V-0	-	288	30

% - Corresponds to Unclad values without adhesive. For declad values (single sided) see corresponding grade "KB-3150N"

& - Corresponds to Declad values with adhesive. For Unclad values see corresponding grade designation.

* - With adhesive

X - may be 0, 4

Marking: Company name and material designation on container or wrapper.

Last Updated on 2020-04-27

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"